

TENSION FABRIC SYSTEMS

**THRILL
ING**



INTRO

Transformation. Create tension. Arouse curiosity. The caterpillar pupates and turns into a butterfly. The octopus changes its color to match the background, and the frog, initially living under water, changes its habitat to land. Unique and fascinating processes. Hence, the question is not: transformation or not? But: how can we use it to present products and companies, create tension and reinvent whole rooms? Here are some thrilling answers.

TRANSFOR MATION



TO MAKE
THEIR COCOON,
CATERPILLARS
NEED ABOUT 3 KM
OF SILK STRING.




TENSION FABRIC PROFILE

TECHNICAL FEATURES

Tension fabric systems

16 – 120
mm

Different profile depths



Various frame colors



Silicone edge technology



2 mm profile edge



Illumination optional

Different profile depths. For all requirements.

Our tension fabric frames are available with profile depths from 16–120 mm. They can be powder-coated in various RAL colors on request – for every spatial requirement and color coordination.

Simple and flexible. With silicone edges.

The fabric is fixed into the fabric groove with a silicone edge. This allows for a quick and tool-less exchange of any graphic.

Profile edges. Almost invisible.

Our anodized aluminium frames take a subsidiary role and put your product into the spotlight. There is merely a 2 mm profile edge framing the fabric.

A shining example. Also in quality.

Our high quality light frames are fitted with Power LEDs, which ensure a brilliant, radiating light. Additional advantages: their longevity and energy efficiency.

WALL SOLUTIONS



Elegant aluminium surface | Without system groove | Different profile depths | Silicone edge technology | Single-sided tension fabric

TENSION FABRIC PROFILE

M 1302.01



Aluminium | matt anodized for mounting fabric with M 1313 silicone edge, bracing available
3.49 kg | 6000 mm





TENSION FABRIC PROFILE

M 1309.01



Aluminium | matt anodized for mounting fabric with M 1313 silicone edge for small formats
2.53 kg | 6000 mm



ACCESSORIES



M 1313

SILICONE EDGE

14 × 3 mm, roll with 100 m



M 1335

INTERNAL CORNER CONNECTOR

to connect M 1302 or M 1309



M 1433

WALL RETAINER

with M4 clamp screw, for M 1302



M 1434

WALL RETAINER

with M4 clamp screw, for M 1309

WALL SOLUTIONS

Single-sided





TENSION FABRIC PROFILE

M 1607.01



Aluminium | matt anodized for mounting fabric with M 1313 silicone edge for small formats up to DIN A1
2.06 kg | 6000 mm





TENSION FABRIC PROFILE

M 1614.00



Aluminium | without surface coating for mounting fabric with M 1313 silicone edge for mounting on wood
1.63 kg | 6000 mm





TENSION FABRIC PROFILE

M 1601.01



Aluminium | matt anodized for mounting fabric with M 1313 silicone edge for small formats up to DIN A1
2.16 kg | 6000 mm




ACCESSORIES



M 1313

SILICONE EDGE

14 x 3 mm, roll with 100 m



M 1927

INTERNAL CORNER CONNECTOR

for M 1601



M 1619

CORNER CONNECTOR

for M 1607

WALL SOLUTIONS

Single-sided




**DID YOU KNOW THAT
POLYESTER FABRIC WAS
DEVELOPED AS A SUBSTITUTE
FOR SILK IN THE 1930S?**

WALL AND CEILING SOLUTIONS



Elegant aluminium surface | With or without system groove | Silicone edge technology | single or double-sided

TENSION FABRIC PROFILE

M 1305.01




Aluminium | matt anodized for mounting fabric with M 1313 silicone edge, single or double-sided
8.70 kg | 6000 mm





TENSION FABRIC PROFILE










M 1302.01



Aluminium | matt anodized for mounting fabric with M 1313 silicone edge, bracing available
3.49 kg | 6000 mm




ACCESSORIES

	M 1313	SILICONE EDGE 14 x 3 mm, roll with 100 m		M 1336	END PLATE for bracing of M 1302
	Z 965B	CORNER CONNECTOR for M 1305		M 1337	EYEBOLT for vertical ceiling suspension
	M 1312	U-PROFILE for bracing of M 1302		M 1338	THREADED PLATE for bracing of M 1302 in connection with M 1312
	M 1314	CONNECTOR for bracing of M 1302 in connection with M 1312		E 218	EYE BOLT for M 1305, max capacity 45 kg
	M 1335	CORNER CONNECTOR for connection of M 1302			

WALL AND CEILING SOLUTIONS


Single-sided | Double-sided



OCTALUMINA – LIGHT FRAMES



Elegant aluminium surface | With or without system groove | Different profile depths | Shadow-free illumination | Brilliant brightness | Silicone edge technology

TENSION FABRIC PROFILE 120 MM DOUBLE-SIDED




M 1901.01

Aluminium | matt anodized
for double-sided light frames,
fabric mounting with M 1313
silicone edge
10.1 kg | 6000 mm





TENSION FABRIC PROFILE 120 MM SINGLE-SIDED




M 1915.01

Aluminium | matt anodized
for single-sided light frames,
fabric mounting with M 1313
silicone edge
13.1 kg | 6000 mm





TENSION FABRIC PROFILE 80 MM DOUBLE-SIDED









M 1925.01

Aluminium | matt anodized
for double-sided light frames,
fabric mounting with M 1313
silicone edge
6.86 kg | 6000 mm




on request

ACCESSORIES


	M 1313 SILICONE EDGE 14 × 3 mm, roll with 100 m		Z 990 CORNER CONNECTOR for M 1915
	Z 965B CORNER CONNECTOR for M 1901 and M 1915		M 1208 ROUND EXTRUSION bracing for M 1901
	M 1965B CORNER CONNECTOR for M 1925 and M 1935		Z 4400 EXTRUSION bracing for M 1915 and M 1935

LIGHT FRAMES

Single-sided | Double-sided





TENSION FABRIC PROFILE
80 MM SINGLE-SIDED



M 1935.01

Aluminium I matt anodized for single-sided light frames, for lateral feed-in, fabric mounting with M 1313 silicone edge 9.6 kg l 6000 mm





TENSION FABRIC PROFILE
60 MM



M 1910.01

Aluminium I matt anodized for single-sided light frames, for mounting LEDs on the rear cover, fabric mounting with M 1313 silicone edge 7.62 kg l 6000 mm





TENSION FABRIC PROFILE
60 MM




M 1920.01

Aluminium I matt anodized for single-sided light frames, for mounting LEDs on the rear cover, fabric mounting with M 1313 silicone edge, fixation to wall 6.07 kg l 6000 mm





TENSION FABRIC PROFILE
40 MM SINGLE-SIDED




M 1930.01

Aluminium I matt anodized for single-sided light frames, for mounting LEDs on the rear cover, fabric mounting with M 1313 silicone edge, fixation to wall 3.43 kg l 6000 mm





TENSION FABRIC PROFILE
40 MM SINGLE-SIDED



M 1970.01

Aluminium I matt anodized for single-sided light frames, for mounting LEDs on the rear cover, fabric mounting with M 1313 silicone edge 4.36 kg l 6000 mm









LIGHT FRAMES

Single-sided




ACCESSORIES

	Z 966 CORNER CONNECTOR for M 1935		M 1927 CORNER CONNECTOR for M 1920, M 1930, and M 1970
	M 1926 CORNER CONNECTOR for M 1920		Z 990 CORNER CONNECTOR for M 1910 and M 1915
	M 1965B CORNER CONNECTOR for M 1925 and M 1935		Z 4400 EXTRUSION for M 1915 and M 1935

FREE-STANDING DISPLAYS



Elegant aluminium surface | With system groove | Different profile depths | Silicone edge technology
Single or double-sided

TENSION FABRIC PROFILE 40 MM




M 1307.01

Aluminium | matt anodized
for single or double-sided
light frames, fabric mounting
with M 1313 silicone edge
5.62 kg | 6000 mm





TENSION FABRIC PROFILE 80 MM



M 1304.01

Aluminium | matt anodized
for single or double-sided
light frames, fabric mounting
with M 1313 silicone edge
10.67 kg | 6000 mm



ACCESSORIES

	Z 965B CORNER CONNECTOR for M 1304		M 1347/SK MOUNTING SCREWS for M 1347 and M 1357
	W 916 CORNER CONNECTOR for M 1307 (straight cut)		M 1347 BASE PLATE FOR M 1307 L 320 x W 120 x H 8 mm screws not included
	Z 990 CORNER CONNECTOR for M 1307 and M 1304		M 1357 BASE PLATE L 320 x W 300 x H 8 mm screws not included
	VA 1240 BROCHURE SHELF rotatable, with mounting materials		M 1498 LED LONG ARM SPOTLIGHT 12W/230V/4000K with 3000 mm cable, incl. retainer M 1481

FREE-STANDING DISPLAYS


Single-sided | Double-sided



CURVED TENSION FABRIC FRAMES



Elegant aluminium surface | With system groove | Silicone edge technology | Double-sided | Radii from 1000 mm

TENSION FABRIC PROFILE 40 MM CURVED




M 1307.01

Aluminium | matt anodized
for single/double-sided mounting
of fabric with M 1313
silicone edge,
smallest radius 1000 mm
5.94 kg | 6000 mm





TENSION FABRIC PROFILE 40 MM CURVED







M 1305.01

Aluminium | matt anodized
for single/double-sided mounting
of fabric with M 1313
silicone edge,
smallest radius 1000 mm
8.70 kg | 6000 mm



ACCESSORIES

	M 1313	SILICONE EDGE 14 x 3 mm, roll with 100 m
	Z 965B	CORNER CONNECTOR for M 1305
	Z 990	CORNER CONNECTOR for M 1307
	W 916	CORNER CONNECTOR for M 1307 (straight cut)

FREE-STANDING DISPLAYS

Curved single-sided | Double-sided

**DID YOU KNOW THAT
ALUMINIUM WEIGHS ONLY
ONE THIRD OF STEEL?**



CUBES



Quick assembly | Silicone edge technology

TENSION FABRIC PROFILE M 1504.01



for illumination



Aluminium | matt anodized fabric mounting with M 1313 silicone edge with 2 fabric grooves
4.57 kg | 6000 mm



CORNER CONNECTOR M 1535.31





Plastic | to connect the M 1504 tension fabric profile
0.06 kg






TENSION FABRIC PROFILE M 1332.01






Aluminium | matt anodized fabric mounting with M 1313 silicone edge with 2 fabric grooves
5.94 kg | 6000 mm




ACCESSORIES

	M 1313	SILICONE EDGE 14 × 3 mm, roll with 100 m
	M 1545	ADAPTOR for double-sided bracing for M 1504
	M 1547	ADAPTOR for single-sided bracing for M 1504

	M 1233	CONNECTION SET for system groove
	Z 460	EXTRUSION for illumination element
	M 1329	ADAPTOR for M 1332


CUBES



ADAPTION PROFILES



Elegant aluminium surface | With system groove | Different profile depths | Silicone edge technology | double-sided

ADAPTION PROFILE 40 MM




M 1310.01

Aluminium | matt anodized with consecutive borings Ø 18 mm, connected to system groove with M 1345
2.76 kg | 6000 mm





ADAPTION PROFILE 80 MM




M 1325.01

Aluminium | matt anodized with consecutive borings Ø 18 mm, connected to system groove with M 1345
5.41 kg | 6000 mm





ADAPTION PROFILE 120 MM



M 1330.01

Aluminium | matt anodized with consecutive borings Ø 18 mm, connected to system groove with M 1345
8.45 kg | 6000 mm



ACCESSORIES



M 1313

SILICONE EDGE

14 x 3 mm, roll with 100 m



M 1345


HAMMERHEAD SCREW

to mount M 1310, M 1325, M 1330 to system groove


TENSION FABRIC FRAMES

Adaption profiles


M 1310
WITH M 1000




WITH M 1020




WITH M 225




M 1325
WITH M 1000




WITH M 1020




WITH M 225




M 1330
WITH M 1000



WITH M 1020



WITH M 225





ADAPTION PROFILE



M 1321.01

Aluminium I matt anodized with consecutive borings 8,9 × 18 mm for direct mounting to system groove with M 1348 to 40 mm square extrusions, as well as 80 mm and 120 mm square extrusions with M 1339 and M 1348
2.92 kg l 6000 mm





ADAPTION PROFILE



M 1319.35

Plastic I light gray with 2 fabric grooves, to mount fabric with M 1313 silicone edge
1.46 kg l 6000 mm




ACCESSORIES



M 1313

SILICONE EDGE

14 × 3 mm, roll with 100 m



M 1339

RETAINER

used in connection with M 1348 for square extrusions with 80 mm and 120 mm



M 1348

HAMMERHEAD SCREW

only for mounting M 1322, M 1322/E, M 1322/I, M 1321

**THE QUALITY OF IMAGES
PRODUCED BY SUBLIMATION
PRINTING CORRESPONDS TO
PHOTO-LIKE QUALITY.**

TENSION FABRIC FRAMES

Adaption profiles






ADAPTION PROFILE




M 1322.01

Aluminium I matt anodized with 11 borings 8,9 × 18 mm for mounting to system groove with M 1348 to 40 mm square extrusions, as well as 80 mm and 120 mm square extrusions with M 1339 and M 1348
2.61 kg l 6000 mm





ADAPTION PROFILE OUTER CORNER




M 1322/E.01

Aluminium I matt anodized with 11 borings 8,9 × 18 mm for mounting to system groove with M 1348 to 40 mm square extrusions, as well as 80 mm and 120 mm square extrusions with M 1339 and M 1348
4.42 kg l 6000 mm





ADAPTION PROFILE INNER CORNER



M 1322/I.01

Aluminium I matt anodized with 11 borings 8,9 × 18 mm for mounting to system groove with M 1348 to 40 mm square extrusions, as well as 80 mm and 120 mm square extrusions with M 1339 and M 1348
4.61 kg l 6000 mm



ACCESSORIES



M 1313

SILICONE EDGE


14 × 3 mm, roll with 100 m



M 1348

HAMMERHEAD SCREW

only for mounting M 1322, M 1322/E, M 1322/I, M 1321



M 1339


RETAINER

used in connection with M 1348 for square extrusions with 80 mm and 120 mm

TENSION FABRIC FRAMES

Adaption profiles





EXHIBITION SYSTEMS
PROJECT SOLUTIONS
PRESENTATION
INTERIOR DESIGN
CLEANROOM SYSTEMS

OCTANORM® UK

RTD Systems Ltd.
Unit 10
Mole Business Park
Randalls Road
Leatherhead
KT22 7BA

T. 020 8545 2945

F. 020 8545 2955

sales@rtdsystems.co.uk

www.rtdsystems.co.uk